



CK-4

Super high performance diesel engine oil

API CK-4 / ACEA E11-22

Available viscosity grades:

15W-40

CK-4 is the oil we made for your modern low-emission diesel engines in trucks, buses, construction, and mining. It is made with quality base oils and the the exact additives for engines requiring CK-4 and ACEA E9 specifications and manufactured according to the European Engine Quality Management System (EELQMS) standards. We tested it in Vietnam's hot and wet conditions to be sure. We got your back on every trip.

PACKAGING UNIT:



TECHNICAL DATA:

Technical Specifications	ASTM	15W-40
Density at 20°C (kg/L)	D4052	0.874
Kinematic Viscosity at 100°C (cSt)	D7042	14.94
Viscosity Index	D2270	130
Flash Point, Open Cup (°C)	D92	240
Pour Point (°C)	D97	-30
Total Base Number – TBN (mg KOH/g)	D2896	9.8
Foaming characteristics at 93.5°C(mL/mL)	D892	10/0

PERFORMANCE LEVELS:

- API CK-4
- API SN
- ACEA E11-22
- ACEA E9-22
- Renault RLD-3
- MTU Type 2.1
- MB-Approval 228.31
- Ford M2C171-F
- Mack EO-S 4.5
- Volvo VDS-4.5
- Deutz DQC III-10 LA
- Cummins CES 20086